



LISEGA 's Interface to AVEVA 's E3D (PDMS)




1. LISEGA's interfaces for AVEVA's E3D – “Model-Area”

- Import routine for LISEGA supports
- LISEGA's “Rod's and Nuts”
- special pipe clamps tool
- part list generation
- helptools for steelwork design (stiffeners and anchor plates)
- LISEGA's clash checker



2. LISEGA's interfaces for AVEVA's E3D – “Draw-Area”


- Explanation of LISEGA's support drawing tool for AVEVA's E3D




1.1 LISEGA's import routine the standard import LIF – export LOF workflow

Workflow of the interface E3D (PDMS) via PLUGIN

Start situation



LICAD Input File (LIF)

LISEGA INTERFACE [LIF] (© 18 Werk 2002)

Current ATTA < /05LAE32BQ114 > File Output < 05LAE32BQ114.lif >

☒ **STATIC** ☐ **DYNAMIC**

StaticLoad

Load: 0.87

Hydro: 1.2

DynamicLoad

Load (H): 0

Load (HZ): 0

Load (HS): 0

StaticMovements

X-Movement: 83

Y-Movement: -98

Z-Movement: -157

DynamicMovements

Positive: 0

Negative: 0

Elevation

Elev. Point 1: 74880

Elev. Point 2: 0

Width: 0

Connection

☒ 1 Elevation Point

☐ 2 Elevation Points

Units


☒ METRIC [MM]

☐ IMPERIAL [INCH]


SET UDA's CE WRITE LIF-FILE CANCEL

In the start situation we find an ATTA on the pipe and some steelwork. After pressing the Export LIF-Button the window for extracting the LIF-file open. The relevant UDA's of the ATTA are transferred directly. Individual decisions should be done in this step (for example type of support; number of elevation points; Unit-system;) although some changes in the load or movement field. After this the button "WRITE LIF-FILE" open the next step "saving the LIF-FILE".


LICAD Main Menu




LICAD Input




After implementing the project and the specifications in the LICAD-Software, the “DESIGNER” in the LISEGA-software “LICAD 10” must be opened. Press the button “Read Support Data From File” gives the possibility to read all data’s from the LIF-File.



Generation of LICAD Output Files (LOF)




Selection of LICAD Output File (LOF)




After pressing the Import LOF-Button the window for implementing the LOF-file is open.


Result of pipe support design



After marking the actual LOF-File, press the “Start LICAD-LOF-File”-Button and the support is designed.

Workflow of support design in PDMS






1.2 LISEGA's import routine the OPEN LICAD PLUGIN

Workflow of the interface E3D (PDMS) via LOF-File

Start situation



LICAD Input File (LIF)

LicadPlugin

Attachment

/11LBQ11BQ012

Restraint

No matching restraint found

☒ First Elevation Point

unset

☐ Second Elevation Point

unset

CE

↺

107617

↻

CE

↺

0

↻

Elevation Point

Width between steels

☒ Add elements around

Restraint within a range of 500 mm

Design with LICAD



Import LOF-File

Remarks



None

After you mark the ATTA press the “CE”-Button, fill in the range of the volume you want to have on the screen, and press the “DESIGN with LICAD”-Button

Automatic transfer of E3D/(PDMS)-information



... LICAD open automatically the "DESIGN-Screen", all data's are available in one step, after pressing the ...






1.3 LISEGA's Rods & Nuts

How to use it?

1.3 LISEGA's Rods & Nuts


If the hanger is modified, it is necessary to connect the hanger with this routine, otherwise it might be that the position of nuts or the length of the threaded rod is incorrect. After marking the restraint use the CE-Button to include restraint (more than one restraint is although possible), if all restraints are included use the "SET LISEGA RODS&NUTS"-Button.





1.4 LISEGA's SPECIAL PIPE CLAMPS


How to use it?



1.4 LISEGA's SPECIAL PIPE CLAMPS

After choosing the ATTA choose the type of special pipe clamp, sub type, material, loadgroup and if available weight and identnumber should be chosen or filled in ...


... press the "CREATE"-Button ...





1.4 LISEGA's SPECIAL PIPE CLAMPS

Fill in the geometric parameters and
"OK"


... press the "CREATE"-Button ...





1.5 LISEGA's Part List Generator


How to use it?




1.5 LISEGA's Part List Generator

Choose the needed language and if required the secondary steelwork ...

... press the "OK"-button ...




Restraint	Quantity	Description	Order-No.	Material
11LBQ11BQ014/RE	2	Anschweissöse	752112	S235
11LBQ11BQ014/RE	2	Federhänger	211118	n,A
11LBQ11BQ014/RE	2	Gewindebügel	612912	P235
11LBQ11BQ014/RE	2	Gewindestück	672113	S235
11LBQ11BQ014/RE	2	Gewindeöse	602912	P235
11LBQ11BQ014/RE	4	Sechskantmutter M12	632928	GüT
11LBQ11BQ014/RE	1	Vertikalschelle	341412R	S235
11LBQ11BQ014/RE	2	Gewindestange	672313	S235
11LBQ11BQ014/RE	1	Anschweissöse	753112-HD	S355
11LBQ11BQ014/RE	1	Federhänger	213118-HD	n,A
11LBQ11BQ014/RE	1	Gewindebügel	613912-HD	P235
11LBQ11BQ014/RE	1	Gewindestück	673113-HD	S235
11LBQ11BQ014/RE	1	Gewindeöse	603912-HD	P235
11LBQ11BQ014/RE	1	Rohrschelle DA 114,3	421119-HD-S	S235
11LBQ11BQ014/RE	2	Sechskantmutter M16	633928	GüT
11LBQ11BQ014/RE	1	Gewindestange	673613	S235
11LBQ11BQ014/RE	1	Anschweissbock	354913	S355
11LBQ11BQ014/RE	1	Gelenkstrebe	394124	n,A
11LBQ11BQ014/RE	1	Sechsellastschelle	361111-LG4-S	S235




1.6 LISEGA's Steelwork support


How to use it?



1.6 LISEGA's Steelwork support


After chosen the connection to steel, picking the hang and picking the section, press the button "CREATE" and a pair of stiffener is created automatically in the hierarchy of the restraint.






1.6 LISEGA's Steelwork support


After chosen the connection to steel and picking the hang, press the button "CREATE" and a pair of stiffener is created automatically in the hierarchy of the restraint.






1.7 LISEGA's Clash Check for supports

How to use it?




1.7 LISEGA's Clash Check for supports

After choosing the relevant restraint, press the "APPLY"-Button for starting the routine in the picture the clashes



1.8 LISEGA's Extras

We include the standard AVEVA-functions "measure" and "add around ce"



Please never forget...

...piping can never be better than its supports!

